



Inv.: Willson et al. Atty: Kenneth C. Brooks (512) 339-7760 ANNOTATED MARKED-UP DRAWING





Inv.: Willson et al.
Atty: Kenneth C. Brooks (512) 339-7760

ANNOTATED MARKED-UP DRAWING






APP. NO.: 09/905,718 Inv.: Willson et al.

Inv.: Willson et al.
Atty: Kenneth C. Brooks (512) 339-7760

ANNOTATED MARKED-UP DRAWING






APP. NO.: 09/905,718 Inv.: Willson et al.

Atty: Kenneth C. Brooks (512) 339-7760
ANNOTATED MARKED-UP DRAWING

 Apply electric field and maintain uniform gap to induce the liquid to adhere

to the template



- Separate the template from the substrate.
- Etch to break-through UV cured liquid, followed by RIE etch transfer into transfer layer to obtain high-aspect ratio structure









FIG. 24



Inv.: Willson et al. Atty: Kenneth C. Brooks (512) 339-7760 ANNOTATED MARKED-UP DRAWING

Apply electric field and maintain uniform gap to induce the liquid to be attracted to the template without making contact



Etch to break-through UV cured liquid, followed by RIE etch transfer into transfer layer to obtain high-aspect ratio structure







FIG. 35




APP. NO.: 09/905,718
Inv.: Willson et al.
Atty: Kenneth C. Brooks (512) 339-7760
ANNOTATED MARKED-UP DRAWING





Inv.: Willson et al.
Atty: Kenneth C. Brooks (512) 339-7760 ANNOTATED MARKED-UP DRAWING






Exhibit A